

3309 (Focus View) Series

- [3309 \(Focus View\) Specifications and Dimensions](#)
- [3309 \(Focus View\) Ordering](#)


3309 (Focus View) Specifications and Dimensions

Specifications


Relative Humidity


100% condensing, non-submersible when connectors are protected

Imperial/US




MS3309	XX	—	AXX	—	BXX	—	CXX	—	DXX	—	EXX
MS330901	1/4-28 UNF thread, No armor										
MS330902	1/4-28UNF thread, With armor										
			Unthreaded Length		Overall Case Length		Total Length		Connector & Cable-Type		Agency Approval
			Order in increments Of 0.1"		Order in increments Of 0.1"						
			Example: 05=0.5"		Example: 35=3.5"		05 0.5 meter/20"		01 Miniature coaxial connector, connector protector & standard cable		00 Not required
			Minimum unthreaded Length: 0.0 in		Minimum unthreaded Length: 0.8"		10 1.0 meter/39"		02 Miniature coaxial connector & standard cable		05 Multiple Approvals
			Maximum unthreaded 9.9"		Maximum unthreaded: 9.9"		50 5 meter/16.4'		11 Miniature coaxial Connector,connector Protector & fluid block cable		
							70 7.0 meter/23.0'		12 Miniature coaxial Connector&fluid Block cable		






Metric





MS3309	XX	—	AXX	—	BXX	—	CXX	—	DXX	—	EXX
MS330903	M8 x 1 thread, no armor										
MS330904	M8 x 1 thread, with armor										
			Unthreaded Length		Overall Case Length		Total Length		Connector & Cable-Type		Agency Approval
			Order in increments Of 10 mm		Order in increments Of 10 mm		05 0.5 meter/20"		01 Miniature coaxial connector, connector protector & standard cable		00 Not required
			Example: 06=60 mm		Example: 06=60 mm		10 1.0 meter/39"		02 Miniature coaxial connector & standard cable		05 Multiple Approvals
			Minimum unthreaded Length: 0 mm		Minimum unthreaded Length: 20 mm		50 5 meter/16.4'		11 Miniature coaxial Connector, connector Protector & fluid block cable		
			Maximum unthreaded length: 230 mm		Maximum unthreaded length: 250 mm		70 7.0 meter/23.0'		12 Miniature coaxial Connector&fluid Block cable		




	MS3309	XX	XX	XX	XX	XX	
MS330905	M10 x 1 thread, No armor						
MS330910	M10 x 1 thread, With armor						
	Unthreaded Length		Overall Case Length		Total Length	Connector & Cable-Type	Agency Approval
	Order in increments Of 10 mm		Order in increments Of 10 mm		05 0.5 meter/20"	01 Miniature coaxial connector, connector protector & standard cable	00 Not required
	Example: 06=60 mm		Example: 06=60 mm		10 1.0 meter/39"		
	Minimum unthreaded Length: 0 mm		Minimum unthreaded Length: 20 mm		50 5 meter/16.4'	02 Miniature coaxial connector & standard cable	05 Multiple Approvals
	Maximum unthreaded 9.9"		Maximum unthreaded: 9.9"		70 7.0 meter/23.0'	11 Miniature coaxial Connector,connector Protector & fluid block cable	
						12 Miniature coaxial Connector&fluid Block cable	


Reverse Mount - Metric or Imperial





Extension Cables





MS330930

Cable Length

Connector and Cable

Agency Approval

040 4.0 meter/13.1'	00 No stainless steel armor	00 Not required
045 4.5 meter/14.8'	01 Stainless steel armor & FEP jacket	05 Multiple Approvals
060 6.0 meter/19.7'	02 Stainless steel armor, no FEP jacket	
065 6.5 meter/21.3'		

3309 (Focus View) Ordering

Imperial/US

Standard Option Descriptions

Model	A: Unthreaded Length	B: Overall Case Length	C: Total Length	D: Connector & Cable Type	E: Agency Approval
MS330901 ¼-28 UNF thread, no armor	Order in increments of 0.1 in	Order in increments of 0.1 in	05 = 0.5 Meter/20 in	01 = Miniature coaxial connector, connector protector & standard cable	00 = Not Required
MS330902 ¼-28 UNF thread, with armor	Example: 05 = 0.5 in	Example: 35 = 3.5 in	10 = 1.0 meter/39 in	02 = Miniature coaxial connector & standard cable	05 = Multiple Approvals
MS330908 ¾-28 UNF thread, no armor	Minimum unthreaded length: 0 mm	Minimum unthreaded length: 20 mm	50 = 5.0 meter/16.4 feet	11 = Miniature coaxial connector, connector protector & fluid block cable	
MS330909 ¾-24 UNF thread, with armor	Maximum unthreaded length: 230 mm	Maximum unthreaded length: 250 mm	70 = 7.0 meter/23.0 feet	12 Miniature coaxial connector & fluid block cable	

Metric

Standard Option Descriptions

Model	A: Unthreaded Length	B: Overall Case Length	C: Total Length	D: Connector & Cable Type	E: Agency Approval
MS330903 M8 x 1 thread, no armor	Order in increments of 10 mm	Order in increments of 10 mm	05 = 0.5 Meter/20 in	01 = Miniature coaxial connector, connector protector & standard cable	00 = Not Required

MS330904 M8 x 1 thread, with armor	Example: 06 = 60 mm	Example: 06 = 60 mm	10 = 1.0 meter/39 in	02 = Miniature coaxialconnector &standard cable	05 = Multiple Approvals
MS330905 M10 x 1 thread, no armor	Minimum unthreaded length: 0 mm	Minimum unthreaded length: 20 mm	50 = 5.0 meter/16.4 feet		
MS330910 M10 x 1 thread, with armor	Maximum unthreaded length: 230 mm	Maximum unthreaded length: 250 mm	90 = 9.0 meter/29.5 feet		

Reverse Mount

Option Descriptions
 MS330906-02-12-CXX-DXX-EXX
 MS330907-05-30-CXX-DXX-EXX

Model	AA: Total Length	BB: Connector & Cable Type	CC: Agency Approval
MS330906-02-12 3⁄8-24 UNF threads	05 = 0.5 meter/20 in	01 = Miniature coaxial connector, connector protector & standard cable	00 = Not Required
MS330907-05-30 M10 x 1 threads	10 = 1.0 meter/39 in	02 = Miniature coaxial connector & standard cable	05 = Multiple Approvals
	50 = 5.0 meter/16.4 feet		
	90 = 9.0 meter/29.5 feet		

Extension Cable

Extension Cable Option Descriptions
 MS330930-AXXX-BXX-CXX

Model	AA: Cable Length	BB: Connector & Cable Type	CC: Agency Approval
MS330930	040=4.0 meter/13.1 feet	00 = No stainless steel armor.	00 = Not Required
	045=4.5 meter/14.8 feet	01 = Stainless steel armor & FEP Jacket.	05 = Multiple Approvals
	060=6.0 meter/19.7 feet	02 = Stainless steel armor, no FEP Jacket	
	065=6.5 meter/21.3 feet		
	080=8.0 meter/26.2 feet		
	085=8.5 meter/27.8		

