

# 3000 Ordering

## 3000 Series, 190 Probes

MS19000-XX-XX-XX-XX  
Option Descriptions

Model	AA: Unthreaded Length	BB: Overall Case Length	CC: Total Length	DD: Connector & Cable Type
MS19000 ¼-28 UNF thread, no armor	English	English	Minimum: 06 6 in.	02 with connector
MS19001 ¼-28 UNF thread, with armor	Standard: 00 (0.0 in.)	Standard: 30 (3.0 in.)	Maximum: 36 36 in.	
MS19007 M8x1, no armor	Increment: 05 (0.5 in.)	Increment: 05 (0.5 in.)	Increment: of 6 in	
MS19008 M8x1, with armor	Minimum: 00 (0.0 in.)	Minimum: 11 (1.1 in.)		
	Maximum: 10 (1.0 in.)	Maximum: 96 (9.6 in.)		
	Metric	Metric		
	Standard: 00 (0 mm)	Standard: 07 (70 mm)		
	Increment: 01 (10 mm)	Increment: 01 (10 mm)		
	Minimum: 00 (0.0 mm)	Minimum: 02 (20 mm)		
	Maximum: 02 (20 mm)	Maximum: 25 (250 mm)		

## 3000 Series, 300 Probes

MS30000-XX-XX-XX-XX  
Option Descriptions

Model	AA: Unthreaded Length	BB: Overall Case Length	CC: Total Length	DD: Connector & Cable Type
MS30000 ¾-28 UNF thread, no armor	English	English	Minimum: 06 6 in.	02 with connector

MS30001 3⁄8-24 UNF thread, with armor	Standard: 00 (0.0 in.)	Standard: 30 (3.0 in.)	Maximum: 36 36 in.	
MS30011 M10x1, no armor	Increment: 05 (0.5 in.)	Increment: 05 (0.5 in.)	Increment: of 6 in	
MS30012 M10x1, with armor	Minimum: 00 (0.0 in.)	Minimum: 11 (1.1 in.)		
	Maximum: 10 (1.0 in.)	Maximum: 96 (9.6 in.)		
	<b>Metric</b>	<b>Metric</b>		
	Standard: 00 (0 mm)	Standard: 07 (70 mm)		
	Increment: 01 (10 mm)	Increment: 01 (10 mm)		
	Minimum: 00 (0.0 mm)	Minimum: 02 (20 mm)		
	Maximum: 02 (20 mm)	Maximum: 25 (250 mm)		

## Extension Cable

Model	AA: Cable Length
MS2789-AXXX no armor	108 = 108 in / 9 ft
MS4454-AXXX with armor	120 = 120 in / 10 ft
	132 = 132 in / 11 ft
	144 = 144 in / 12 ft
	156 = 156 in / 13 ft
	168 = 168 in / 14 ft
	180 = 180 in / 15 ft
	192 = 192 in / 16 ft
	204 = 204 in / 17 ft

Revision #3

Created 6 July 2022 18:26:39 by Bach\_L

Updated 9 May 2023 17:36:31 by Bach\_L