

3000 Ordering

3000 Series, 190 Probes

MS Option	Description	XX
MS 001	Option 1: Standard configuration	01
MS 002	Option 2: Advanced configuration	02
MS 003	Option 3: Custom configuration	03
MS 004	Option 4: Special configuration	04
MS 005	Option 5: Experimental configuration	05

Model	AA: Unthreaded Length	BB: Overall Case Length	CC: Total Length	DD: Connector & Cable Type
MS19000 ¼-28 UNF thread, no armor	English	English	Minimum: 06 6 in.	02 with connector
MS19001 ¼-28 UNF thread, with armor	Standard: 00 (0.0 in.)	Standard: 30 (3.0 in.)	Maximum: 36 36 in.	
MS19007 M8x1, no armor	Increment: 05 (0.5 in.)	Increment: 05 (0.5 in.)	Increment: of 6 in	
MS19008 M8x1, with armor	Minimum: 00 (0.0 in.)	Minimum: 11 (1.1 in.)		
	Maximum: 10 (1.0 in.)	Maximum: 96 (9.6 in.)		
	Metric	Metric		
	Standard: 00 (0 mm)	Standard: 07 (70 mm)		
	Increment: 01 (10 mm)	Increment: 01 (10 mm)		
	Minimum: 00 (0.0 mm)	Minimum: 02 (20 mm)		
	Maximum: 02 (20 mm)	Maximum: 25 (250 mm)		

3000 Series, 300 Probes

MS Option	Description	XX
00	Standard	
01	Standard	
02	Standard	
03	Standard	
04	Standard	
05	Standard	
06	Standard	
07	Standard	
08	Standard	
09	Standard	
10	Standard	
11	Standard	
12	Standard	
13	Standard	
14	Standard	
15	Standard	
16	Standard	
17	Standard	
18	Standard	
19	Standard	
20	Standard	
21	Standard	
22	Standard	
23	Standard	
24	Standard	
25	Standard	
26	Standard	
27	Standard	
28	Standard	
29	Standard	
30	Standard	
31	Standard	
32	Standard	
33	Standard	
34	Standard	
35	Standard	
36	Standard	
37	Standard	
38	Standard	
39	Standard	
40	Standard	
41	Standard	
42	Standard	
43	Standard	
44	Standard	
45	Standard	
46	Standard	
47	Standard	
48	Standard	
49	Standard	
50	Standard	
51	Standard	
52	Standard	
53	Standard	
54	Standard	
55	Standard	
56	Standard	
57	Standard	
58	Standard	
59	Standard	
60	Standard	
61	Standard	
62	Standard	
63	Standard	
64	Standard	
65	Standard	
66	Standard	
67	Standard	
68	Standard	
69	Standard	
70	Standard	
71	Standard	
72	Standard	
73	Standard	
74	Standard	
75	Standard	
76	Standard	
77	Standard	
78	Standard	
79	Standard	
80	Standard	
81	Standard	
82	Standard	
83	Standard	
84	Standard	
85	Standard	
86	Standard	
87	Standard	
88	Standard	
89	Standard	
90	Standard	
91	Standard	
92	Standard	
93	Standard	
94	Standard	
95	Standard	
96	Standard	
97	Standard	
98	Standard	
99	Standard	

Model	AA: Unthreaded Length	BB: Overall Case Length	CC: Total Length	DD: Connector & Cable Type
MS30000 ⅜-28 UNF thread, no armor	English	English	Minimum: 06 6 in.	02 with connector

MS30001 3⁄8-24 UNF thread, with armor	Standard: 00 (0.0 in.)	Standard: 30 (3.0 in.)	Maximum: 36 36 in.	
MS30011 M10x1, no armor	Increment: 05 (0.5 in.)	Increment: 05 (0.5 in.)	Increment: of 6 in	
MS30012 M10x1, with armor	Minimum: 00 (0.0 in.)	Minimum: 11 (1.1 in.)		
	Maximum: 10 (1.0 in.)	Maximum: 96 (9.6 in.)		
	Metric	Metric		
	Standard: 00 (0 mm)	Standard: 07 (70 mm)		
	Increment: 01 (10 mm)	Increment: 01 (10 mm)		
	Minimum: 00 (0.0 mm)	Minimum: 02 (20 mm)		
	Maximum: 02 (20 mm)	Maximum: 25 (250 mm)		

Extension Cable

Model	AA: Cable Length
MS2789-AXXX no armor	108 = 108 in / 9 ft
MS4454-AXXX with armor	120 = 120 in / 10 ft
	132 = 132 in / 11 ft
	144 = 144 in / 12 ft
	156 = 156 in / 13 ft
	168 = 168 in / 14 ft
	180 = 180 in / 15 ft
	192 = 192 in / 16 ft
	204 = 204 in / 17 ft

Revision #3

Created 6 July 2022 18:26:39 by Bach_L

Updated 9 May 2023 17:36:31 by Bach_L