

# 3000 Ordering

## 3000 Series, 190 Probes

MS Option	Description	XX
00	None	
01	1000	
02	2000	
03	3000	
04	4000	
05	5000	
06	6000	
07	7000	
08	8000	
09	9000	
10	10000	
11	11000	
12	12000	
13	13000	
14	14000	
15	15000	
16	16000	
17	17000	
18	18000	
19	19000	
20	20000	
21	21000	
22	22000	
23	23000	
24	24000	
25	25000	
26	26000	
27	27000	
28	28000	
29	29000	
30	30000	
31	31000	
32	32000	
33	33000	
34	34000	
35	35000	
36	36000	
37	37000	
38	38000	
39	39000	
40	40000	
41	41000	
42	42000	
43	43000	
44	44000	
45	45000	
46	46000	
47	47000	
48	48000	
49	49000	
50	50000	
51	51000	
52	52000	
53	53000	
54	54000	
55	55000	
56	56000	
57	57000	
58	58000	
59	59000	
60	60000	
61	61000	
62	62000	
63	63000	
64	64000	
65	65000	
66	66000	
67	67000	
68	68000	
69	69000	
70	70000	
71	71000	
72	72000	
73	73000	
74	74000	
75	75000	
76	76000	
77	77000	
78	78000	
79	79000	
80	80000	
81	81000	
82	82000	
83	83000	
84	84000	
85	85000	
86	86000	
87	87000	
88	88000	
89	89000	
90	90000	
91	91000	
92	92000	
93	93000	
94	94000	
95	95000	
96	96000	
97	97000	
98	98000	
99	99000	

Model	AA: Unthreaded Length	BB: Overall Case Length	CC: Total Length	DD: Connector & Cable Type
MS19000 ¼-28 UNF thread, no armor	English	English	Minimum: 06 6 in.	02 with connector
MS19001 ¼-28 UNF thread, with armor	Standard: 00 (0.0 in.)	Standard: 30 (3.0 in.)	Maximum: 36 36 in.	
MS19007 M8x1, no armor	Increment: 05 (0.5 in.)	Increment: 05 (0.5 in.)	Increment: of 6 in	
MS19008 M8x1, with armor	Minimum: 00 (0.0 in.)	Minimum: 11 (1.1 in.)		
	Maximum: 10 (1.0 in.)	Maximum: 96 (9.6 in.)		
	Metric	Metric		
	Standard: 00 (0 mm)	Standard: 07 (70 mm)		
	Increment: 01 (10 mm)	Increment: 01 (10 mm)		
	Minimum: 00 (0.0 mm)	Minimum: 02 (20 mm)		
	Maximum: 02 (20 mm)	Maximum: 25 (250 mm)		

## 3000 Series, 300 Probes

MS Option	Description	XX
00	None	
01	1000	
02	2000	
03	3000	
04	4000	
05	5000	
06	6000	
07	7000	
08	8000	
09	9000	
10	10000	
11	11000	
12	12000	
13	13000	
14	14000	
15	15000	
16	16000	
17	17000	
18	18000	
19	19000	
20	20000	
21	21000	
22	22000	
23	23000	
24	24000	
25	25000	
26	26000	
27	27000	
28	28000	
29	29000	
30	30000	
31	31000	
32	32000	
33	33000	
34	34000	
35	35000	
36	36000	
37	37000	
38	38000	
39	39000	
40	40000	
41	41000	
42	42000	
43	43000	
44	44000	
45	45000	
46	46000	
47	47000	
48	48000	
49	49000	
50	50000	
51	51000	
52	52000	
53	53000	
54	54000	
55	55000	
56	56000	
57	57000	
58	58000	
59	59000	
60	60000	
61	61000	
62	62000	
63	63000	
64	64000	
65	65000	
66	66000	
67	67000	
68	68000	
69	69000	
70	70000	
71	71000	
72	72000	
73	73000	
74	74000	
75	75000	
76	76000	
77	77000	
78	78000	
79	79000	
80	80000	
81	81000	
82	82000	
83	83000	
84	84000	
85	85000	
86	86000	
87	87000	
88	88000	
89	89000	
90	90000	
91	91000	
92	92000	
93	93000	
94	94000	
95	95000	
96	96000	
97	97000	
98	98000	
99	99000	

Model	AA: Unthreaded Length	BB: Overall Case Length	CC: Total Length	DD: Connector & Cable Type
MS30000 ⅜-28 UNF thread, no armor	English	English	Minimum: 06 6 in.	02 with connector

MS30001 3⁄8-24 UNF thread, with armor	Standard: 00 (0.0 in.)	Standard: 30 (3.0 in.)	Maximum: 36 36 in.	
MS30011 M10x1, no armor	Increment: 05 (0.5 in.)	Increment: 05 (0.5 in.)	Increment: of 6 in	
MS30012 M10x1, with armor	Minimum: 00 (0.0 in.)	Minimum: 11 (1.1 in.)		
	Maximum: 10 (1.0 in.)	Maximum: 96 (9.6 in.)		
	<b>Metric</b>	<b>Metric</b>		
	Standard: 00 (0 mm)	Standard: 07 (70 mm)		
	Increment: 01 (10 mm)	Increment: 01 (10 mm)		
	Minimum: 00 (0.0 mm)	Minimum: 02 (20 mm)		
	Maximum: 02 (20 mm)	Maximum: 25 (250 mm)		

## Extension Cable

Model	AA: Cable Length
MS2789-AXXX no armor	108 = 108 in / 9 ft
MS4454-AXXX with armor	120 = 120 in / 10 ft
	132 = 132 in / 11 ft
	144 = 144 in / 12 ft
	156 = 156 in / 13 ft
	168 = 168 in / 14 ft
	180 = 180 in / 15 ft
	192 = 192 in / 16 ft
	204 = 204 in / 17 ft

Revision #3

Created 6 July 2022 18:26:39 by Bach\_L

Updated 9 May 2023 17:36:31 by Bach\_L